



Bundbohrbuchsen DIN 172 Form A



Bestellbeispiel	811.172.095.20
Bohrbuchse	811.
DIN 172 Form A	172.
d1 = 9,5mm	095.
l1 = 20,0mm	20

ø Bohrung d1	ø Außen d2	ø Bund d3	l1		l2 Bundhöhe
			kurz	mittel lang	
DIN-Stufungen: 0.1 / 0.25 / 0.75					
Alle Maße in mm					
0.4 bis 0.8	3	6	6	2	
0.9 bis 1.0			6		
			9		
1.1 bis 1.8	4	7	6		
			9		
1.9 bis 2.6	5	8	6		
			9		
2.7 bis 3.3	6	9	8		
			12		
			16		
3.4 bis 4.0	7	10	8	2.5	
			12		
			16		
4.1 bis 5.0	8	11	8		
			12		
			16		
5.1 bis 6.0	10	13	10		
			16		
			20		
6.1 bis 8.0	12	15	10	3	
			16		
			20		
8.1 bis 10.0	15	18	12		
			20		
			25		
10.1 bis 12.0	18	22	12	4	
			20		
			25		
12.1 bis 15.0	22	26	16		
			28		
			36		
DIN-Stufungen 0.5 mm					
15.5 bis 18.0	26	30	16	4	
			28		
			36		
18.5 bis 22.0	30	34	20		
			36		
			45		
22.5 bis 26.0	35	39	20		
			36		
			45		
26.5 bis 30.0	42	46	25	5	
			45		
			56		
30.5 bis 35.0	48	52	25		
			45		
			56		
35.5 bis 42.0	55	59	30		
			56		
			67		
42.5 bis 48.0	62	66	30		
			56		
			67		
48.5 bis 55.0	70	74	30		
			56		
			67		
55.5 bis 63.0	78	82	35	6	
			67		
			78		
63.5 bis 70.0	85	90	35		
			67		
			78		
70.5 bis 78.0	95	100	40		
			78		
			105		

Zylindrische Bohrbuchsen DIN 179 Form A



Bestellbeispiel	810.179.095.20
Bohrbuchse	810.
DIN 179 Form A	179.
d1 = 9,5mm	095.
l1 = 20,0mm	20

l3 = Länge der Einführfase an ø2
r = Radius an ø1

ø Bohrung d1	ø Außen d2	l1		l3 Fase	r Radius
		kurz	mittel lang		
DIN-Stufungen: 0.1 / 0.25 / 0.75					
Alle Maße in mm					
0.4 bis 0.8	3	6	1	1	
0.9 bis 1.0		6			
		9			
1.1 bis 1.8	4	6	1	1	
		9			
1.9 bis 2.6	5	6	1	1	
		9			
2.7 bis 3.3	6	8	1	1	
		12			
		16			
3.4 bis 4.0	7	8	1	1	
		12			
		16			
4.1 bis 5.0	8	8	1	1	
		12			
		16			
5.1 bis 6.0	10	10	1.25	1.5	
		16			
		20			
6.1 bis 8.0	12	10	1.25	1.5	
		16			
		20			
8.1 bis 10.0	15	12	1.5	2	
		20			
		25			
10.1 bis 12.0	18	12	1.5	2	
		20			
		25			
12.1 bis 15.0	22	16	1.5	2	
		28			
		36			
DIN-Stufungen 0.5 mm					
15.5 bis 18.0	26	16	1.5	2	
		28			
		36			
18.5 bis 22.0	30	20	2.5	3	
		36			
		45			
22.5 bis 26.0	35	20	2.5	3	
		36			
		45			
26.5 bis 30.0	42	25	2.5	3	
		45			
		56			
30.5 bis 35.0	48	25	2.5	3	
		45			
		56			
35.5 bis 42.0	55	30	3	3.5	
		56			
		67			
42.5 bis 48.0	62	30	3	3.5	
		56			
		67			
48.5 bis 55.0	70	30	3	3.5	
		56			
		67			
55.5 bis 63.0	78	35	3	4	
		67			
		78			
63.5 bis 70.0	85	35	3	4	
		67			
		78			
70.5 bis 78.0	95	40	3	4	
		78			
		105			

Bohrbuchsen DIN 172 und 179 Form B (Radius oben und unten) sowie Sonderabmessungen auf Anfrage.